

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version 001      Revision Date: 29.07.2024      SDS Number: NSK-SDS-002-GB(EN)      Date of last issue: 20.11.2023  
Date of first issue: 20.11.2023

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : PANA SPRAY Plus

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Lubricant

Recommended restrictions  
on use : Not applicable

#### 1.3 Details of the supplier of the safety data sheet

Company : NSK Europe  
Elly-Beinhorn-Strasse 8  
65760 Eschborn, Germany

Telephone : +49 6196 77606 0

E-mail address of person  
responsible for the SDS : info@nsk-europe.de

#### 1.4 Emergency telephone number

+81(0)289-62-5636 (8:00-17:00,JST)

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Specific target organ toxicity - single ex-  
posure, Category 3

H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version 001      Revision Date: 29.07.2024      SDS Number: NSK-SDS-002-GB(EN)      Date of last issue: 20.11.2023  
Date of first issue: 20.11.2023

---

- Hazard pictograms :  
- Signal word : Danger
- Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H336 May cause drowsiness or dizziness.
- Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
**Response:**  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
**Storage:**  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Hazardous components which must be listed on the label:

Butane  
Propane  
Isobutane

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

May displace oxygen and cause rapid suffocation.

---

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version 001      Revision Date: 29.07.2024      SDS Number: NSK-SDS-002-GB(EN)      Date of last issue: 20.11.2023  
Date of first issue: 20.11.2023

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Butane	106-97-8 203-448-7 601-004-00-0	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336	>= 30 - < 50
Ethanol	64-17-5 200-578-6 603-002-00-5	Flam. Liq. 2; H225 Eye Irrit. 2; H319  specific concentration limit Eye Irrit. 2; H319 >= 50 %	>= 30 - < 50
Propane	74-98-6 200-827-9 601-003-00-5	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336	>= 20 - < 30
Isobutane	75-28-5 200-857-2 601-004-00-0	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336	>= 10 - < 20

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.  
If not breathing, give artificial respiration.  
If breathing is difficult, give oxygen.  
Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2023
001	29.07.2024	NSK-SDS-002-GB(EN)	Date of first issue: 20.11.2023

---

Rinse mouth thoroughly with water.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause drowsiness or dizziness.

Gas reduces oxygen available for breathing.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Remove all sources of ignition.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2023
001	29.07.2024	NSK-SDS-002-GB(EN)	Date of first issue: 20.11.2023

---

Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Avoid breathing spray.  
Do not swallow.  
Avoid contact with eyes.  
Avoid prolonged or repeated contact with skin.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version 001      Revision Date: 29.07.2024      SDS Number: NSK-SDS-002-GB(EN)      Date of last issue: 20.11.2023  
Date of first issue: 20.11.2023

---

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.  
Do not spray on an open flame or other ignition source.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.

Advice on common storage : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives  
Gases

Recommended storage temperature : < 40 °C

### 7.3 Specific end use(s)

Specific use(s) : No data available

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Butane	106-97-8	OELV - 15 min (STEL)	1,000 ppm	IE OEL
Ethanol	64-17-5	OELV - 15 min	1,000 ppm	IE OEL

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version 001      Revision Date: 29.07.2024      SDS Number: NSK-SDS-002-GB(EN)      Date of last issue: 20.11.2023  
Date of first issue: 20.11.2023

Isobutane	75-28-5	(STEL) OELV - 15 min (STEL)	1,000 ppm	IE OEL
-----------	---------	-----------------------------------	-----------	--------

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Ethanol	Workers	Inhalation	Long-term systemic effects	950 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	343 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	114 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	206 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	87 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Ethanol	Fresh water	0.96 mg/l
	Freshwater - intermittent	2.75 mg/l
	Marine water	0.79 mg/l
	Sewage treatment plant	580 mg/l
	Fresh water sediment	3.6 mg/kg dry weight (d.w.)
	Marine sediment	2.9 mg/kg dry weight (d.w.)
	Soil	0.63 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	380 mg/kg food

## 8.2 Exposure controls

### Engineering measures

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

### Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:  
Safety glasses  
Equipment should conform to I.S. EN 166

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version 001	Revision Date: 29.07.2024	SDS Number: NSK-SDS-002-GB(EN)	Date of last issue: 20.11.2023 Date of first issue: 20.11.2023
----------------	------------------------------	-----------------------------------	---

---

determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Skin and body protection : Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.  
Equipment should conform to I.S. EN 137

Filter type : Self-contained breathing apparatus

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state : Aerosol containing a liquefied gas

Propellant : Butane, Propane, Isobutane

Colour : clear

Odour : odourless

Odour Threshold : No data available

Melting point/freezing point : -187.7 - -138.4 °C

Initial boiling point and boiling range : -42.1 - -0.5 °C

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower : No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2023
001	29.07.2024	NSK-SDS-002-GB(EN)	Date of first issue: 20.11.2023

---

flammability limit

Flash point : 13 °C  
Flash point is only valid for liquid portion in the aerosol can.

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Solubility(ies)  
Water solubility : soluble

Partition coefficient: n-  
octanol/water : Not applicable

Vapour pressure : 2,480 - 12,750 hPa (40 °C)

Relative density : No data available

Density : 0.549 g/cm<sup>3</sup> (20 °C)

Relative vapour density : Not applicable

Particle characteristics  
Particle size : Not applicable

### 9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : 1.8 - 9.5

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2023
001	29.07.2024	NSK-SDS-002-GB(EN)	Date of first issue: 20.11.2023

---

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Not classified as a reactivity hazard.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.  
Vapours may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

#### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **Butane:**

Acute inhalation toxicity : LC50 (Rat): 570000 ppm  
Exposure time: 15 min  
Test atmosphere: gas  
Remarks: Based on data from similar materials

##### **Ethanol:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2023
001	29.07.2024	NSK-SDS-002-GB(EN)	Date of first issue: 20.11.2023

---

Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

### Propane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm  
Exposure time: 15 min  
Test atmosphere: gas

### Isobutane:

Acute inhalation toxicity : LC50 (Rat): 570000 ppm  
Exposure time: 15 min  
Test atmosphere: gas

### Skin corrosion/irritation

Not classified based on available information.

### Components:

#### Ethanol:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

### Components:

#### Ethanol:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irritation to eyes, reversing within 21 days

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

### Components:

#### Ethanol:

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2023
001	29.07.2024	NSK-SDS-002-GB(EN)	Date of first issue: 20.11.2023

---

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

#### Ethanol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: Ingestion  
Result: equivocal

#### Propane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

#### Isobutane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version 001	Revision Date: 29.07.2024	SDS Number: NSK-SDS-002-GB(EN)	Date of last issue: 20.11.2023 Date of first issue: 20.11.2023
----------------	------------------------------	-----------------------------------	---

---

Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **Butane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

#### **Ethanol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Mouse  
Application Route: Ingestion  
Result: negative

#### **Propane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2023
001	29.07.2024	NSK-SDS-002-GB(EN)	Date of first issue: 20.11.2023

---

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

### Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

### STOT - single exposure

May cause drowsiness or dizziness.

#### Components:

##### Butane:

Assessment : May cause drowsiness or dizziness.  
Remarks : Based on data from similar materials

##### Propane:

Assessment : May cause drowsiness or dizziness.

##### Isobutane:

Assessment : May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified based on available information.

### Repeated dose toxicity

#### Components:

##### Butane:

Species : Rat  
NOAEL :  $\geq 9000$  ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version 001      Revision Date: 29.07.2024      SDS Number: NSK-SDS-002-GB(EN)      Date of last issue: 20.11.2023  
Date of first issue: 20.11.2023

---

### Ethanol:

Species : Rat  
NOAEL : 1,280 mg/kg  
LOAEL : 3,156 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

### Propane:

Species : Rat  
NOAEL : 7.214 mg/l  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

### Isobutane:

Species : Rat  
NOAEL : >= 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

### Aspiration toxicity

Not classified based on available information.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### Ethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia (water flea)): > 1,000 mg/l  
Exposure time: 48 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version 001	Revision Date: 29.07.2024	SDS Number: NSK-SDS-002-GB(EN)	Date of last issue: 20.11.2023 Date of first issue: 20.11.2023
----------------	------------------------------	-----------------------------------	---

---

Toxicity to algae/aquatic plants : ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l  
Exposure time: 72 h  
  
EC10 (Chlorella vulgaris (Fresh water algae)): 11.5 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): 6,500 mg/l  
Exposure time: 16 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 9.6 mg/l  
Exposure time: 9 d  
Species: Daphnia magna (Water flea)

### 12.2 Persistence and degradability

#### Components:

##### **Butane:**

Biodegradability : Result: Readily biodegradable.  
Remarks: Based on data from similar materials

##### **Ethanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 84 %  
Exposure time: 20 d

##### **Propane:**

Biodegradability : Result: Readily biodegradable.  
Remarks: Based on data from similar materials

##### **Isobutane:**

Biodegradability : Result: Readily biodegradable.  
Remarks: Based on data from similar materials

### 12.3 Bioaccumulative potential

#### Components:

##### **Butane:**

Partition coefficient: n-octanol/water : log Pow: 2.89

##### **Ethanol:**

Partition coefficient: n-octanol/water : log Pow: -0.35

##### **Propane:**

Partition coefficient: n-octanol/water : log Pow: 2.36



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2023
001	29.07.2024	NSK-SDS-002-GB(EN)	Date of first issue: 20.11.2023

---

### Isobutane:

Partition coefficient: n-  
octanol/water : log Pow: 2.8

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.  
Do not dispose of waste into sewer.

Contaminated packaging : Please ensure aerosol cans are sprayed completely empty (including propellant)  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version 001      Revision Date: 29.07.2024      SDS Number: NSK-SDS-002-GB(EN)      Date of last issue: 20.11.2023  
Date of first issue: 20.11.2023

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

**ADN** : UN 1950  
**ADR** : UN 1950  
**RID** : UN 1950  
**IMDG** : UN 1950  
**IATA** : UN 1950

#### 14.2 UN proper shipping name

**ADN** : AEROSOLS  
**ADR** : AEROSOLS  
**RID** : AEROSOLS  
**IMDG** : AEROSOLS  
**IATA** : Aerosols, flammable

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 2	2.1
<b>ADR</b>	: 2	2.1
<b>RID</b>	: 2	2.1
<b>IMDG</b>	: 2.1	
<b>IATA</b>	: 2.1	

#### 14.4 Packing group

**ADN**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

**RID**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 2.1

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version 001	Revision Date: 29.07.2024	SDS Number: NSK-SDS-002-GB(EN)	Date of last issue: 20.11.2023 Date of first issue: 20.11.2023
----------------	------------------------------	-----------------------------------	---

EmS Code : F-D, S-U

### IATA (Cargo)

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### IATA (Passenger)

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 75  
If you intend to use this product as tattoo ink, please contact your vendor.

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the condi-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2023
001	29.07.2024	NSK-SDS-002-GB(EN)	Date of first issue: 20.11.2023

---

				tions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable		
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable		
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	:	Not applicable		
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	:	Not applicable		
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable		
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.				
P3a	FLAMMABLE AEROSOLS	Quantity 1 150 t	Quantity 2 500 t	
18	Liquefied flammable gases (including LPG) and natural gas	50 t	200 t	

### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

---

## SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

### Full text of H-Statements

H220 : Extremely flammable gas.  
H225 : Highly flammable liquid and vapour.  
H280 : Contains gas under pressure; may explode if heated.  
H319 : Causes serious eye irritation.  
H336 : May cause drowsiness or dizziness.

### Full text of other abbreviations

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2023
001	29.07.2024	NSK-SDS-002-GB(EN)	Date of first issue: 20.11.2023

Eye Irrit.	:	Eye irritation
Flam. Gas	:	Flammable gases
Flam. Liq.	:	Flammable liquids
Press. Gas	:	Gases under pressure
STOT SE	:	Specific target organ toxicity - single exposure
IE OEL	:	List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1 and 2
IE OEL / OELV - 15 min (STEL)	:	Occupational exposure limit value (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Aerosol 1	H222, H229
STOT SE 3	H336

### Classification procedure:

Based on product data or assessment  
Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878

## PANA SPRAY Plus

Version	Revision Date:	SDS Number:	Date of last issue: 20.11.2023
001	29.07.2024	NSK-SDS-002-GB(EN)	Date of first issue: 20.11.2023

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

IE / EN